



| Pos | Part Number | Description | Additional Text | Quantity |
|-----|----------------|------------------------------|-----------------|----------|
| 1 | 6030300120033 | FRAME "603 OA" BLACK | | 1.00 |
| 2 | 6030300200033 | SUB FRAME | | 1.00 |
| 3 | 6030300600033S | ENGINE SUPPORT R/S BLACK | | 1.00 |
| 4 | 6030300500033S | ENGINE SUPPORTL/S BLACK | | 1.00 |
| 5 | 6030304800033S | FOOTR. SUP. REAR L/S BLACK | | 1.00 |
| 6 | 6030304900033S | FOOTR. SUP. REAR R/S BLACK | | 1.00 |
| 7 | 60312010050 | SUITCASE HOOK L/S | | 1.00 |
| 8 | 60312010060 | DAMPING RUBBER SUITCASE HOOK | | 1.00 |
| 9 | 60312011050 | SUITCASE HOOK R/S | | 1.00 |
| 10 | 60312011060 | DAMPING RUBBER SUITCASE HOOK | | 1.00 |
| 11 | 6030508400033S | EXHAUST BRACKET | | 1.00 |

| | | | | |
|----|----------------|--------------------------------|-------------------|-------|
| 12 | 61305068000 | DAMPING RUBBER | | 1.00 |
| 13 | 60312021250 | CASE BAR R/S | | 1.00 |
| 14 | 60312020250 | CASE BAR L/S | | 1.00 |
| 15 | 54633037000 | WASHER 8MM GALVANIZED | | 1.00 |
| 16 | 0025080306 | HH collar screw M8x30 | | 6.00 |
| 17 | 60303002058 | SPACER BUSHING 13X17X8,2 | | 10.00 |
| 18 | 0025060356 | HH collar screw M6x35 TX30 | | 2.00 |
| 19 | 0021060003 | Washer DIN9021-A 6.4 | ONLY USA | 2.00 |
| 20 | 60307048000 | RUBBER SEAT-CONTACT SURFACE | | 4.00 |
| 21 | 0025080506 | HH collar screw M8x50 TX40 | | 1.00 |
| 22 | 60305069000 | BUSHING | | 2.00 |
| 23 | 60307040041 | PLATE RUBBER SEAT | | 2.00 |
| 24 | 60307049000 | BUSH 6.2X12X21.5 | | 4.00 |
| 25 | 60303007000 | SPACER BUSH ENGINE SUPPORT | | 2.00 |
| 26 | 54603048100 | clip nut M6 | | 2.00 |
| 27 | 0035100209 | AH collar screw M10x20 ISA45 | | 2.00 |
| 28 | 76009062000 | Special screw M8X25 SL TX40 | | 4.00 |
| 29 | 60003040133 | FOOTPEG LS+RS CPL. | | 1.00 |
| 30 | 54603041000 | FOOTREST SPRING L/S & R/S | | 2.00 |
| 31 | 60003040010 | FOOTREST RUBBER FRONT L/S 03 | | 1.00 |
| 32 | 60003041010 | FOOTREST RUBBER FRONT R/S 03 | | 1.00 |
| 33 | 54803044000 | PIN FOR FOOT PED 51.5X9.8 MM | FE | 2.00 |
| 34 | 0125100003 | washer DIN 125 A 10.5 | ONLY FOR 640 DUKE | 2.00 |
| 35 | 59003040250 | FOOT PEG L/S SILVER 02 | SX RACING | 1.00 |
| 36 | 59003041250 | FOOT PEG R/S SILVER 02 | SX RACING | 1.00 |
| 37 | 6030310109533S | FOOTREST MOUNTING | | 2.00 |
| 38 | 0094032253 | PIN DIN0094-3,2X25 STEEL | | 2.00 |
| 39 | 0025080166S | HH collar screw M8x16 TX40 SL | | 4.00 |
| 40 | 60003044010 | CLOSING PANEL FRONT L/S R/S 03 | | 2.00 |
| 41 | 0985050003 | Self locking nut DIN 985 M5 | | 2.00 |
| 42 | 61007014000 | SPACER FUEL TANK 05 | | 2.00 |
| 43 | 0019080456 | countersunk screw M8x45 TX45 | | 1.00 |
| 44 | 0025060306 | HH collar screw M6x30 TX30 | | 2.00 |
| 45 | 60303070000 | CHAIN GUIDE | | 1.00 |
| 46 | 0024060156 | HH collar screw M6x15 TX30 | ONLY USA | 1.00 |
| 47 | 0934080003 | Hexagon nut DIN934 M8 | | 1.00 |
| 48 | 58303070100 | BUMP RUBBER M8X25MM | | 1.00 |
| 49 | 54603048200 | RANGE CHANGE METAL NUT M5 | | 2.00 |
| 51 | 69008021160 | special screw M5x12 | | 1.00 |
| 52 | 0035100509S | AH collar screw M10x50 ISA45 | ONLY ADVENTURE R | 2.00 |
| 54 | 0035100249 | AH collar screw M10x24 ISA45 | | 10.00 |
| 55 | 60003152000 | ENGAGE PANEL FOOTREST L/S 03 | | 2.00 |
| 56 | 60003052000 | ENGAGE PANEL FOOTREST R/S 03 | | 2.00 |
| 57 | 60003050000 | FOOTREST CPL. L/S REAR 03 | | 1.00 |
| 58 | 60003051000 | FOOTREST CPL. R/S REAR 03 | | 1.00 |
| 59 | 60003044100 | footrest bolt, rear | | 2.00 |
| 60 | 0799060003 | retaining washer DIN 6799 - 6 | | 2.00 |
| 61 | 60308024200 | TRIPLECLAMP-FACEPLATE BELOW | | 1.00 |
| 62 | 83008000015 | SPECIAL SCREW M6X15X3 | | 2.00 |
| 63 | 6030319000030 | SKID PLATE ADV | | 1.00 |
| 64 | 0025060406 | HH collar screw M6x40 TX30 | | 2.00 |

| | | | | |
|----|-------------|-----------------------------|--|------|
| 65 | 45239060050 | COLLAR BUSHING 6,3X8X13X9,5 | | 2.00 |
| 66 | 60003096000 | VIBRATION DAMPER 03 | | 2.00 |
| 67 | 60303003010 | STEERING HEAD COVER | | 1.00 |
| 68 | 0025080356 | HH collar screw M8x35 TX40 | | 2.00 |
| 69 | 0025080256 | HH collar screw M8x25 | | 1.00 |