

ACHTUNG
Lesen Sie vor der ersten Inbetriebnahme des Fahrzeuges die gesamte Bedienungsanleitung aufmerksam durch!

IMPORTANT
Please read the entire owner's manual carefully before putting the vehicle into operation for the first time.

ATTENZIONE
Prima della messa in funzione iniziale del veicolo, leggere con attenzione l'intero manuale d'uso!

ATTENTION
Lire attentivement l'ensemble du manuel d'utilisation avant de mettre le véhicule en service!

ATENCIÓN
Lea completa y atentamente el manual de instrucciones antes de poner en servicio por primera vez el vehículo!

1

890 Duke R 636 03 098 000

Fuel: RON 95 unleaded (USA = PREMIUM RON 91)
Tyre front: 120/70 ZR17 M/C (59W)
Air pressure front: rider only 2.3 bar (33 psi)
max. payload 2.3 bar (33 psi)
Tyre rear: 180/55 ZR17 M/C (73W)
Air pressure rear: rider only 2.5 bar (36 psi)
max. payload 2.5 bar (36 psi)
Max payload: 160kg (353lbs)
Max. total weight: 430kg (948lbs)
Engine oil: fully synthetic 10W/50 (5W/40 under 0°C, 32°F)

Further information see owner's manual

2

25mm

2-5mm

641.04.099.000

3

SETTING
look owner's manual

	FORK		SHOCK	
	Compression	Rebound	Comp. low speed	Comp. high speed (dual)
Comfort	20	20	16	17
Standard	16	16	14	14
Sport	4	10	10	12
Max. payload	15	15	14	11

4

5

6

7

8

Pos	Part Number	Description	Additional Text	Quantity
1	50307098000	STICKER "OWNERS MANUAL"		1.00
2	63603098000	Tech. info. sticker		1.00
3	64104099000	Sticker chain tension		1.00
4	63603097000	Sticker, STD setting		1.00
5	LI20-636-12	Typeplate CANADA		1.00
6	LI20-636-11	Typeplate USA KTM		1.00
7	LI21-636-13	Noise emission label USA		1.00
8	LI21-636-6	Emission control information 5		1.00